

四合一气体检测仪

4 IN 1 GAS MONITOR

SW-7500D

项目 ITEMS	基础款 Basic	旗舰款 Flagship
显示屏幕 Screen	2.4英寸彩屏 / 2.4" Color LCD	
传感器原理 Sensor Principle	电化学式和催化燃烧式/ Electrochemical and Catalytic Combustion	
报警功能 Alarm	声音/灯光/振动三种报警模式/ Three alarm modes: Sound/light/vibration	
报警值设定 Alarm Setting	上下限报警值/ Upper and lower limit alarm value	
响应时间 Response Time	<30s	
气种显示模式 Gas Type Display Mode	组合显示, 单气显示任意选择/ Combination display, Single gas display	
采样方式 Sampling Method	泵吸式/Built-in air pump	
时间显示 Time Display	√	
示值误差 Reading Error	±5%FS	
语音播报 Voice Broadcast	中文/英文 Chinese/English	
支持语言 Language	中文/英文 Chinese/English	
数据存储 Storage Function	400组/Units	
电池规格 Battery	3.7V 3000mAh锂电池 Li-ion	
充电规格 Charging Specification	DC 5V/ 1A Type-C USB接口/Interface	
充电时长 Charging Time	约4小时/About 4 hours	
满电续航 Battery Life	约6小时/About 6 hours	
自动关机 Auto Power-off	5分钟 (无任何操作情况下, 可手动取消) / 5 minutes (be canceled if no operation)	
工作温湿度 Working Temperature/Humidity	-10°C~50°C; ≤95%RH	
储存温湿度 Storage Temperature/Humidity	-20°C~60°C; ≤85%RH	
防爆等级 Explosion-proof Certification	Ex ib IIB T3 Gb	
防护等级 Protection Grade	IP54	
采集手柄 Retractable detection handle	×	√
机身尺寸 Dimension	174x77x55mm	



常规气体检测范围 Conventional Gas Detection Range

气体种类 Gas Type	量程 Range	分辨率 Resolution	低报警点Low Concentration Alarm Value	高报警点High Concentration Alarm Value
CO	0~1000 µmol/mol	1 µmol/mol	50 µmol/mol	150 µmol/mol
H ₂ S	0~100 µmol/mol	1 µmol/mol	10 µmol/mol	35 µmol/mol
O ₂	0~30% VOL	0.1% VOL	19.5% VOL	23.5% VOL
Ex	0~100% LEL	1% LEL	20% LEL	50% LEL

深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.
地址: 东莞市虎门镇虎门团结路58号深达威科技园
Add: Sndway Science & Technology Industrial Park, 58
Tuanjie Road, Humen 523930, Dongguan, China
邮箱/E-mail: market@sndway.com
全国咨询热线/Service Hotline: 400-125-6969
网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网/WEB



关注公众号