

里氏硬度计

LEEB HARDNESS METER

SW-6210S(标准版/Standard)

项目 ITEMS	参数 SPECIFICATIONS
显示屏幕 Screen	2.4寸128x64黑白点阵屏 2.4" Black and White Dot Matrix LCD
冲击装置 Impact Device	D型/Standard Type D
测量精度 Accuracy	±6HL@760HLD, ±10HL@530HLD
测量范围 Measurement Range	170~960HLD
测量方向 Measuring Direction	垂直向下(Vertical down)、斜下(Diagonal down)、水平(Horizontal)、斜上(Diagonal up)、垂直向上(Vertical up)
硬度测量材料 Hardness Measuring Material	钢和铸钢(Steel and cast steel)、合金工具钢(Alloy tool steel)、不锈钢(Stainless steel)、灰铸铁(Gray cast iron)、球墨铸铁(Nodular cast iron)、铸铝合金(Cast aluminum alloy)、铜锌合金(黄铜)Copper-zinc alloy (Brass)、铜锡合金(青铜) Copper-zinc alloy (Brass)、纯铜Copper-tin alloy (Bronze)、锻钢(Forged steel)
强度测量材料 Intensity Measuring Material	低碳钢(Low carbon steel)、高碳钢(High carbon steel)、铬钢(Chromium steel)、铬钒钢(Chromium vanadium steel)、铬镍钢(Chromiumnickel steel)、铬钼钢(Chromium molybdenum steel)、铬镍钼钢(Chromium nickel molybdenum steel)、铬锰硅钢(Chromium manganese silicon steel)、超高强度钢(Ultrahigh strength steel)、不锈钢(Stainless steel)
硬度制式 Hardness Unit	里氏(HL)、布氏(HB)、洛氏B(HRB)、洛氏C(HRC) 洛氏A(HRA)、维氏(HV)、肖氏(HS)
标准硬度块 Standard Hardness Sample	√
储存容量 Max Storage	800组(冲击次数32~1) / 800 units(Impact Times 32~1)
电池类型 Battery	3.7V 2000mAh锂电池 Li-ion
充电规格 Charging Specifications	DC 5V/0.5A Type-C USB接口 / Interface
工作环境 Work Environment	周围环境无强烈振动(No strong vibration)、无强烈磁场(No strong magnetic field)、无腐蚀性介质及严重粉尘(No corrosive medium and serious dust in the surrounding environment)
存储温度 Storage Temperature	-10℃~50℃
工作温度 Working Temperature	0℃~40℃
存储湿度 Storage Humidity	10% ~ 70%RH
外形尺寸 Product Dimension	140x66x28.5mm
外箱尺寸 Carton MEAS	298x268x258mm
装箱数量 QTY per Carton	10 PCS
重量 G.W per Carton	5.7KG



深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.
 地址: 东莞市虎门镇虎门团结路58号深达威科技园
 Add: Sndway Science & Technology Industrial Park, 58
 Tuanjie Road, Humen 523930, Dongguan, China
 邮箱/E-mail: market@sndway.com
 全国咨询热线/Service Hotline: 400-125-6969
 网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网/WEB



关注公众号