

涂层测厚仪

COATING THICKNESS METER

SW-6300A/B

项目 ITEMS	SW-6300A	SW-6300B
测量范围 Measurement Range	磁性(Magnetism) 0~1200μm; 非磁性(Non-magnetism) 0~1200μm	磁性(Magnetism) 0~1700μm; 非磁性(Non-magnetism) 0~1700μm
中文语音播报 Chinese Voice Prompt	×	√
测量精度 Accuracy	±(2+2%*H)μm @ (0~500μm); ±(2.5%*H)μm @ (> 500μm)	
分辨率 Resolution	0.1μm @ (0~99.9μm); 1μm @ (≥100μm)	
最小测量区域 Min. Measurement Area	磁性(Magnetism)25x25mm; 非磁性(Non-magnetism)25x25mm	
最小曲率 Min. Curvature	凸面(Convexity)5mm; 凹面(Concavity)30mm	
最小底材厚度 Min. Thickness of Substrate	磁性(Magnetism)0.2mm; 非磁性(Non-magnetism)0.05mm	
显示屏 Screen	反显段码屏/Reverse Video Segment LCD	
电池类型 Battery	3.7V 850mAh锂电池 Li-ion	
充电规格 Charging Specifications	DC 5V/0.8A Type-C接口/Interface	
存储温度 Storage Temperature	-10°C~60°C	
存储湿度 Storage Humidity	10% ~ 70%RH	
工作温度 Working Temperature	0°C~50°C	
工作湿度 Working Humidity	10% ~ 80%RH	
外形尺寸 Product Dimension	104x63x28mm	
外箱尺寸 Carton MEAS	445x293x232mm	
装箱数量 QTY per Carton	20 PCS	
重量 G.W per Carton	5.3KG	



深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.
地址: 东莞市虎门镇虎门团结路58号深达威科技园
Add: Sndway Science & Technology Industrial Park, 58
Tuanjie Road, Humen 523930, Dongguan, China
邮箱/E-mail: market@sndway.com
全国咨询热线/Service Hotline: 400-125-6969
网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网/WEB



关注公众号