

涂层测厚仪

COATING THICKNESS METER

SW-6310A

项目 ITEMS	参数 SPECIFICATIONS
显示屏幕 Screen	2.0英寸段码屏 / 2.0" Segment LCD
测量范围 Measurement Range	磁性(Magnetism)0~1700μm; 非磁性(Non-magnetism)0~1700μm
测量精度 Accuracy	±(2+2%*H)μm @ (0~500μm); ±(2.5%*H)μm @ (500~1700μm)
分辨率 Resolution	0.1μm@ (0~99.9μm); 1μm@ (100~1700μm)
最小测量区域 Min. Measurement Area	磁性(Magnetism)25x25mm; 非磁性(Non-magnetism)25x25mm
最小曲率 Min. Curvature	凸面(Convexity)5mm; 凹面(Concavity)30mm
最小底材厚度 Min. Thickness of Substrate	磁性(Magnetism)0.2mm; 非磁性(Non-magnetism)0.05mm
数据存储 Max Storage	30笔/Units
电池类型 Battery	2x1.5V AAA
存储温度 Storage Temperature	-10℃~60℃
工作温度 Working Temperature	0℃~50℃
存储湿度 Storage Humidity	10% ~ 70%RH
外形尺寸 Product Dimension	120x52x26mm
外箱尺寸 Carton MEAS	445x293x232mm
装箱数量 QTY per Carton	20 PCS
重量 G.W per Carton	7.1KG



深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.
地 址: 东莞市虎门镇虎门团结路58号深达威科技园
Add: Sndway Science & Technology Industrial Park, 58
Tuanjie Road, Humen 523930, Dongguan, China
邮箱/E-mail: market@sndway.com
全国咨询服务热线/Service Hotline: 400-125-6969
网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网/WEB



关注公众号