

超声波测厚仪

UITRASONIC THICKNESS METER

SW-6530

项目 ITEMS	参数 SPECIFICATIONS
显示屏幕 Screen	2.4英寸彩屏 / 2.4" Color LCD
支持语音 Language	中文/英文 Chinese/English
测量范围 Measurement Range	1.00~300.00mm(钢中/In steel)
声速范围 Sound Velocity	1000~9999m/s
测量精度 Accuracy	H<10mm, ±0.1mm, H为实际厚度; H≥10mm, ±(1%H+0.1)mm
分辨率 Resolution	0.1mm/0.01mm/0.01in
最大/最小值 Max/Min Value	√
平均值 Average Value	√
打印功能 Printing	√
标准厚度块 Standard Thickness of The Block	4mm
管材测量下限 Lower Limit of Pipe Measurement	Φ20*3mm (钢 / steel)
探头 Probe	5MHz Φ10mm
存储容量 Max Storage	4500笔/Units
存储内容 Storage Contents	当前材料(Material)、声速(Sound Velocity) 单位(Unit)、测量/平均/最大/最小值 (Measured/Average/Max/Min Value)
主要功能 Main Function	单次测量(Single Measurement)、连续测量 (Continuous Measurement)、报警测量(Alarm Measurement)、反测声速(Sound Velocity Measurement)、自助校准(Calibration)
电池类型 Battery	3.7V 1800mAh锂电池 Li-ion
充电规格 Charging Specifications	DC 5V/0.5A Micro USB接口/Interface
存储温度 Storage Temperature	-10°C~50°C
工作温度 Working Temperature	0°C~40°C
存储湿度 Storage Humidity	相对湿度≤90%RH
外形尺寸 Product Dimension	206x80x36.5mm
外箱尺寸 Carton MEAS	325x257x148mm
装箱数量 QTY per Carton	4 PCS
重量 G.W per Carton	4.21KG

