

涂层测厚仪

COATING THICKNESS METER

SW-6310D

项目 ITEMS	参数 SPECIFICATIONS
显示屏幕 Screen	3.5英寸彩屏 / 3.5" Color LCD
测量范围 Measurement Range	磁性(Magnetism)0~1700μm; 非磁性(Non-magnetism)0~1700μm
测量精度 Accuracy	±(2+2%*H)μm @ (0~500μm); ±(2.5%*H)μm @ (500~1700μm)
分辨率 Resolution	0.1μm @ (0~99.9μm); 1μm @ (100~1700μm)
最小测量区域 Min. Measurement Area	磁性(Magnetism)25x25mm; 非磁性(Non-magnetism)25x25mm
最小曲率 Min. Curvature	凸面(Convexity)5mm; 凹面(Concavity)30mm
最小底材厚度 Min. Thickness of Substrate	磁性(Magnetism)0.2mm; 非磁性(Non-magnetism)0.05mm
触摸屏 Touch Screen	√
中文语音播报 Chinese Voice Prompt	√
数据导出 Data Exporting	通过USB连接电脑导出 Communicating with computer via USB cable
数据存储 Max Storage	8组,每组32笔 / 8 Units,32sets/units
电池类型 Battery	3.7V 3500mAh锂电池 Li-ion
充电规格 Charging Specifications	DC 5V/ 2A Type-C USB接口 / Interface
存储温度 Storage Temperature	-10℃~60℃
工作温度 Working Temperature	0℃~50℃
存储湿度 Storage Humidity	10% ~ 70%RH
外形尺寸 Product Dimension	150x70x30mm
外箱尺寸 Carton MEAS	380x235x245mm
装箱数量 QTY per Carton	10 PCS
重量 G.W per Carton	7.5KG

