

壁挂式噪音计

SOUND LEVEL METER

SW-525C/D/G

项目 ITEMS	SW-525C	SW-525D	SW-525G
测量范围 Measurement Range	30~130dB		
精度 Accuracy	±1.5dB(以标准声源为准, 94dB@1KHz) ±1.5dB (In Standard Sound:94dB@1KHz)		
频率响应 Frequency Response	31.5Hz~8.5KHz		
频率计权 Frequency Weighting	A权/A		
响应时间 Response Time	FAST(快)		
麦克风 Microphone	6mm电容式麦克风/6mm Condenser Microphone		
数位显示 Digital Display	3位数 / 3 digits Display		
解析度 Resolution	0.1dB(<100dB), 1dB(>100dB)		
报警提示(声音+显示) Alarm (Sound+Display)	√		
报警输出 Alarm Output	输出DC5V, 可驱动报警喇叭或报警灯/ Output DC5V, drivable alarm horn or alarm light		
存储功能 Storage Function	2秒/笔, 可存一年 2 secs./time, can be stored for a year		
与电脑通信 Communication	通过USB线与电脑通信 Communicating with computer via USB cable		
供电方式 Power Supply	DC5V 2A Type-C		
内置锂电池 Built-in Spare Li-ion	3.7V 4000mAh		
充电时间 Charging Time	约4.5小时/About 4.5 hours		
满电续航 Battery Life	约10小时 About 10 hours	约12小时 About 12 hours	约10小时 About 10 hours
工作温度 Working Temperature	0℃~40℃		
工作湿度 Working Humidity	10% ~ 80%RH		
存储温度 Storage Temperature	-10℃~60℃		
存储湿度 Storage Humidity	10% ~ 70%RH		
外形尺寸 Product Dimension	228x125x33mm		
外箱尺寸 Carton MEAS	480x295x378mm		
装箱数量 QTY per Carton	20 PCS		
重量 G.W per Carton	12.52KG		



深达威科技(广东)股份有限公司

Sndway Technology (Guangdong) co., Ltd.

地址: 东莞市虎门镇虎门团结路58号深达威科技园

Add: Sndway Science & Technology Industrial Park, 58

Tuanjie Road, Humen 523930, Dongguan, China

邮箱/E-mail: market@sndway.com

全国咨询服务热线/Service Hotline: 400-125-6969

网址/Url: www.sndway.com 电话/Tel: 0769-85265688



官网/WEB



关注公众号